



PO 275

Overview

Rigid circular metal sawing machines offering manual, manual with pneumatic vice, or semi-automatic operation. Double self-centring vice prevents break off burrs. Saw head can swivel 45 degrees left and right. Slotting and longitudinal cutting are possible. Protective saw blade guard opens and closes automatically. Saw blade can be replaced quickly and easily.

SPECIFICATION	UNIT	PO 275
Cutting Capacity	Deg	90 45
Tube - Round	mm	80 60
Tube - Square	mm	75 x 75 50 x 50
Tube - Rectangular	mm	90 x 75 60 x 50
Solids - Round	mm	38 25
Solids - Square	mm	38 x 38 25 x 25
Max Clamp Opening	mm	85
Blade Diameter	mm	250 / 275 / 300
Blade Centre Hole Diameter	mm	32
Drive Pins Diameter and PCD	mm	10 x 63
Cutting Speed	Rpm	45 / 90
Motor	Kw	1.3 / 1.8
Machine Length	mm	1000
Machine Width	mm	800
Machine Height	mm	1700
Machine Weight	Kg	220 / 250 / 300

Standard Features

- Double self-centring clamps
- Coolant pump and pedestal
- Two-speed cutting head
- Mitre sawing facility
- Enclosed safety guard

~~\$2,570~~
Reduced to:
\$1,680*

~~\$4,425~~
Reduced to:
\$2,760*



PO 275 PKPD

*1 ONLY PRICE EXCLUDES GST & FREIGHT